

7005 Series | – Dry Erase Laminate

LuminaTM by FDC 7005 Series is a dry erase laminate film specially formulated for use with dry erase materials. This product can be written on repeatedly, then wiped clean with a dry tissue or dry erase cleaning fluid.

Film Technology | Polyester

Film Thickness | 1.0 mil

Color | Clear

Outdoor Durability | 1 Year

Finish | Gloss

Blockout | No

Adhesive | Permanent Solvent

Liner | 78#

Conformability | Flat Surfaces, Simple Curves

Shelf Life | 2 years

<u>CUTTING</u>	<u>PRINTING</u>	<u>INSTALLATION</u>
Computer Cut Yes Steel Rule Yes Thermal Die Yes Flat Bed Yes Sheetable Yes Laminate No	Thermal Transfer No Solvent No Eco-Solvent No Latex No UV No Screen No	Wet Apply No Min. App. Temp. 50°F (Optimum 60 degrees) Interior / Exterior Yes

<p><u>F I L M</u></p> <ul style="list-style-type: none"> • Film Thickness__ (mils/μm) 1.0 mil • Film Weight__ (gsm) N/A • Gloss__ (60°) N/A • Opacity__ (%) N/A • Tensile Strength__ (lbs/in) N/A • Elongation__ (%) N/A • Dimensional Stability__ N/A 	<p><u>A D H E S I V E</u></p> <ul style="list-style-type: none"> • Adhesive Type__ Solvent • Adhesive Thickness__ N/A • Adhesive Color__ Clear • Peel Strength__ (lbs/in) 15 min: 1.9, 24 hrs:2.5
<p><u>L I N E R</u></p> <ul style="list-style-type: none"> • Liner Weight__ (#/gsm) 78# • Liner Type__ Bleached Paper • Liner Thickness__ (mils/μm) N/A • Release Force__ N/A 	<p><u>P E R F O R M A N C E G U I D A N C E</u></p> <ul style="list-style-type: none"> • Application Temp.__ > 50 °F • Service Temp.__ -40 °F to +180 °F • Shelf Life__ 2 years • Storage Temp. / Rel. Humidity__ 73 °F / 50% • Outdoor Durability__ 1 years • Removability__ No

NOTE - For further information regarding printing, substrate cleaning, application, maintenance, durability, and removal please review the corresponding instructional bulletin available at fdcfilms.com.

WARRANTY - Data provided by FDC Graphic Films, Inc. is for general information only. This data is not to be used for exacting specification purposes. Always pre-test the product. Suitability for any given application is the responsibility of the user. Since FDC Graphic Films, Inc. cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety, or applicability with respect hereto. FDC Graphic Films, Inc.'s only obligation shall be to replace such a quantity of product proven to be defective. FDC Graphic Films, Inc. shall not be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or inability to use the product. Before using, the user shall determine the suitability of the product for their intended use, and the user assumes all risk and liability whatsoever in connection therewith. The seller, FDC Graphic Films, Inc., shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, to short or reduced supply of fuel, or other integral components of the product.

<MA>