

7267 Series | Lumina Print Media: Perforated Window, Removable Adhesive

Lumina series 7267 is a perforated calendered vinyl film designed for printed one-way vision window graphics requiring short term durability with clean removal. To order punched material, use color number 102 (50/50) or 402 (60/40) perf. Laminate with Lumina 7004 optically clear.

Film Technology | Calendered - Perforated PVC

Film Thickness | 6 mil

Color | White (102 Matte 50/50, or 402 Matte 60/40 Perforation)

Outdoor Durability | 1 years

Finish | Gloss

Blockout | No

Adhesive | Permanent / Clear

Liner | 95#

Conformability | Flat/Simple Curves

Shelf Life | 1 Year

<u>CUTTING</u>	<u>PRINTING</u>	<u>INSTALLATION</u>
Computer Cut Yes Steel Rule Yes Thermal Die Yes Flat Bed Yes Sheetable Yes Laminate Yes / Cold	Thermal Transfer Yes Solvent Yes Eco-Solvent Yes Latex Yes UV No Screen Yes	Wet Apply No Min. App. Temp. 40°F Interior / Exterior Yes

<p><u>FILM</u></p> <ul style="list-style-type: none"> • Film Thickness__ (mils/μm) 6.0 / 152 (+/- 10%) • Film Weight__ (gsm) 100 • Gloss__ 60° Reflection N/A • Opacity__ (%) N/A • Tensile Strength__ (lbs/in) N/A • Elongation__ N/A • Dimensional Stability__ (FTM 14) MD < 0.30 mm / CD < 0.30 mm 	<p><u>ADHESIVE</u></p> <ul style="list-style-type: none"> • Adhesive Type__ Solvent Acrylic • Adhesive Thickness__ (mils/μm) .08-1.0 / 20-25 • Adhesive Color__ Clear • Peel Strength__ (lbs/in) (N/25mm) 24 hrs. 1.6 / 7.0
<p><u>LINER</u></p> <ul style="list-style-type: none"> • Liner Weight__ (#/gsm) 95 / 160 • Liner Type__ Dual Layer (Perforated/Solid) White 2-Sided PE-Coated Kraft • Liner Thickness__ (mils/μm) 9.2 / 235 • Release Force__ @ 360" / min (g/2") 50-75 	<p><u>PERFORMANCE GUIDANCE</u></p> <ul style="list-style-type: none"> • Application Temp.__ On clean, dry substrate > +40 °F • Service Temp.__ -40 °F to 180 °F • Shelf Life__ up to 1 year • Storage Temp. / Rel. Humidity__ 70°F (21°C) and 50% relative humidity • Outdoor Durability__ up to 3 years • Removability__ Up to 1 year

NOTE - For further information regarding printing, substrate cleaning, application, maintenance, durability, and removal please review the corresponding instructional bulletin available at fdcfilms.com.

WARRANTY - Data provided by FDC Graphic Films, Inc. is for general information only. This data is not to be used for exacting specification purposes. Always pre-test the product. Suitability for any given application is the responsibility of the user. Since FDC Graphic Films, Inc. cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety, or applicability with respect hereto. FDC Graphic Films, Inc.'s only obligation shall be to replace such a quantity of product proven to be defective. FDC Graphic Films, Inc. shall not be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or inability to use the product. Before using, the user shall determine the suitability of the product for their intended use, and the user assumes all risk and liability whatsoever in connection therewith. The seller, FDC Graphic Films, Inc., shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, to short or reduced supply of fuel, or other integral components of the product.

<MA>